

QUALITY
since 1948

PRESSURES PER AGRICULTURAL TYRES

Pressures are given in bars, loads given in kg.
To obtain load per tyre you should weigh the tractor with the implement attached and raised, per drive axles, and divide per 2.

Peace of mind, every time

Kleber

Pressures Per agricultural tyres KLEBER

High volume

KLEBER TOPKER									
Pressures (bar) & Max.load (kg) per Tyre - Take into account the load and type of work when adjusting pressures									
SPEED in km/h	0,6	1,0	1,2	1,6	1,8	2,0	2,4	2,8	Capacity in litres of water 75% max
600/65R28 TL 154A8/154B									
30	1900	2480	2770	3350	3510	3675	3840	4000	405
40		2360	2625	3150	3300	3450	3600	3750	
600/70R28 TL 157A8/157B									
30	2060	2785	3150	3875	4030	4190	4345	4500	470
40		2575	2900	3550	3695	3840	3980	4125	
650/75R38 TL 169A8/169B									
30	2900	3860	4340	5300	5510	5725	5940	6150	709
40		3550	3990	4875	5105	5340	5570	5800	
650/85R38 TL 173A8/173B									
30	3250	4350	4900	6000	6225	6450	6675	6900	821
40		4000	4485	5450	5710	5975	6240	6500	

Low Profile 70

KLEBER FITKER									
Pressures (bar) & Max.load (kg) per Tyre - Take into account the load and type of work when adjusting pressures									
SPEED in km/h	0,4	0,6	0,8	1,0	1,2	1,4	1,6	Capacity in litres of water 75% max	
320/70R24 TL 116A8/116B									
30	620	890	980	1070	1160	1250	1340	105	
40		830	915	1000	1080	1165	1250		
360/70R24 TL 122A8/122B									
30	750	1070	1180	1285	1395	1500	1610	136	
40		990	1090	1195	1295	1400	1500		
380/70R24 TL 125A8/125B									
30	820	1170	1290	1410	1530	1650	1770	160	
40		1090	1200	1315	1425	1540	1650		
420/70R24 TL 130A8/130B									
30	950	1350	1485	1620	1760	1895	2030	203	
40		1250	1380	1510	1640	1770	1900		
480/70R24 TL 138A8/138B									
30	1170	1680	1850	2020	2190	2360	2530	276	
40		1560	1720	1880	2040	2200	2360		
360/70R28 TL 125A8/125B									
30	820	1170	1290	1410	1530	1650	1770	153	
40		1090	1200	1315	1425	1540	1650		
380/70R28 TL 127A8/127B									
30	870	1250	1375	1500	1620	1745	1870	179	
40		1160	1280	1395	1515	1630	1750		
420/70R28 TL 133A8/133B									
30	1020	1470	1615	1760	1910	2055	2200	231	
40		1360	1500	1640	1780	1920	2060		
480/70R28 TL 140A8/140B									
30	1240	1780	1960	2140	2320	2500	2680	302	
40		1650	1820	1990	2160	2330	2500		
480/70R30 TL 141A8/141B									
30	1280	1830	2015	2200	2390	2575	2760	316	
40		1700	1875	2050	2230	2405	2580		
480/70R34 TL 143A8/143B									
30	1360	1940	2135	2330	2530	2725	2920	345	
40		1800	1985	2170	2360	2545	2730		
520/70R34 TL 148A8/148B									
30	1570	2240	2465	2690	2920	3145	3370	422	
40		2080	2295	2510	2720	2935	3150		
480/70R38 TL 145A8/145B									
30	1440	2060	2270	2475	2685	2890	3100	377	
40		1910	2110	2305	2505	2700	2900		
520/70R38 TL 150A8/150B									
30	1670	2380	2620	2860	3100	3340	3580	464	
40		2210	2440	2665	2895	3120	3350		
580/70R38 TL 155A8/155B									
30	1930	2760	3040	3315	3595	3870	4150	590	
40		2560	2825	3090	3350	3615	3880		
620/70R42 TL 160A8/160B									
30	2240	3180	3510	3835	4165	4490	4820	658	
40		2970	3275	3580	3890	4195	4500		

Low profile 65

KLEBER GRIPKER									
Pressures (bar) & Max.load (kg) per Tyre - Take into account the load and type of work when adjusting pressures									
SPEED in km/h	0,6	0,8	1,0	1,2	1,4	1,6	Capacity in litres of water 75% max		
440/65R24 TL 128D									
30	1120	1340	1560	1780	1925	2070	178		
40		1285	1490	1700	1835	1970			
480/65R24 TL 133D									
30	1290	1530	1770	2010	2190	2370	218		
40		1455	1690	1920	2090	2260			
540/65R24 TL 140D									
30	1530	1835	2135	2440	2660	2880	287		
40		1745	2030	2320	2530	2740			
440/65R28 TL 131D									
30	110	1425	1665	1900	2070	2240	198		
40		1355	1580	1810	1975	2140			
480/65R28 TL 136D									
30	1370	1645	1915	2190	2385	2580	242		
40		1560	1820	2080	2265	2450			
540/65R28 TL 142D									
30	1645	1955	2270	2580	2815	3050	318		
40		1855	2150	2450	2675	2900			
540/65R30 TL 143D									
30	1690	2010	2330	2650	2890	3130	333		
40		1915	2220	2520	2750	2980			
540/65R34 TL 145D									
30	1805	2165	2520	2880	3110	3340	364		
40		2060	2400	2740	2960	3180			
600/65R34 TL 151D									
30	2130	2535	2935	3340	3655	3970	464		
40		2415	2800	3180	3480	3780			
540/65R38 TL 147D									
30	1910	2260	2610	2960	3250	3540	394		
40		2155	2490	2820	3095	3370			
600/65R38 TL 153D									
30	2250	2680	3110	3540	3870	4200	500		
40		2555	2960	3370	3685	4000			
650/65R38 TL 157D									
30	2520	3005	3485	3970	4355	4740	602		
40		2855	3320	3780	4150	4520			
650/65R42 TL 158D									
30	2650	3165	3685	4200	4545	4890	646		
40		3015	3510	4000	4325	4650			

Large

KLEBER SUPER 8L **									
Pressures (bar) & Max.load (kg) per Tyre - Take into account the load and type of work when adjusting pressures									
SPEED in km/h	0,6	0,8	1,2	1,6	2,0	2,2	2,4	Capacity in litres of water 75% max	
260/70R16 TL 109A8/106B									
30	440	515	660	805	955	1025	1100	45	
40		410	480	615	755	890	1030		
280/70R16 TL 112A8/109B									
30	490	570	725	885	1040	1120	1200	50	
40		460	535	680	825	975	1045		
280/70R18 TL 114A8/111B									
30	520	600	765	930	1095	1180	1260	52	
40		490	565	720	875	1025	1105		
280/70R20 TL 116A8/113B									
30	550	640	815	990	1165	1250	1340	57	
40		515	595	760	925	1085	1170		
300/70R20 TL 119A8/116B									
30	620	715	900	1085	1275	1365	1460	71	
40		580	665	840	1015	1185	1275		
320/70R20 TL 123A8/120B									
30	670	780	1000	1220	1440	1550	1660	79	
40		630	730	935	1140	1345	1450		
360/70R20 TL 129A8/126B									
30	800	930	1195	1455	1720	1850	1980	112	
40		750	870	1115	1360	1605	1730		
420/70R30 TL 134A8/131B									
30	1230	1440	1645	1855	2060	2270	229		
40		1150	1345	1540	1730	1925	2120		

CAUTION

Use the technical documentation and inflation tables which show the load/pressure figures for different operating speeds.

These load/pressure tables correspond to the tyre deflection allowed by the manufacturer.

If the pressure is incorrect, the tyre is either under or over inflated, which can cause:

- either unsatisfactory performance in the field (grip/load capacity) or unsatisfactory road holding leading to a loss of control;
- or damage (premature casing fatigue)
- or uneven wear that may reduce the life of the tyre.

Apart from correct initial inflation it is also recommended that the pressure be checked periodically and corrected if any air has been lost.

NOTA

We recommend replacing the rubber valve or the seals on the metal at each tyre replacement. The above details are subject to modification after publication (May 2012)

Peace of mind, every time

Kleber

Standard multi-purpose

KLEBER TRAKER									
Pressures (bar) & Max. load (kg) per Tyre - Take into account the load and type of work when adjusting pressures									
SPEED									Capacity in litres
in km/h	0,6	0,8	1,0	1,2	1,4	1,6			of water 75% max
320/85 R20 TL 119A8/116B									
30	950	1050	1155	1255	1360	1460			105
40		980	1075	1170	1265	1360			
250/85 R24 TL 109A8/106B									
30	720	795	870	950	1025	1100			64
40		740	810	885	960	1030			
280/85 R24 TL 115A8/112B									
30	850	940	1030	1120	1210	1300			98
40		870	960	1045	1130	1220			
320/85 R24 TL 122A8/119B									
30	1040	1155	1270	1380	1495	1610			112
40		1080	1185	1290	1395	1500			
340/85 R24 TL 125A8/122B									
30	1150	1275	1400	1520	1645	1770			143
40		1190	1305	1420	1535	1650			
380/85 R24 TL 131A8/128B									
30	1360	1505	1650	1800	1945	2090			180
40		1400	1540	1675	1810	1950			
420/85 R24 TL 137A8/134B									
30	1600	1770	1945	2115	2290	2460			248
40		1660	1820	1980	2140	2300			
250/85 R28 TL 112A8/109B									
30	780	865	950	1030	1115	1200			75
40		810	890	965	1040	1120			
280/85 R28 TL 118A8/115B									
30	920	1020	1115	1215	1310	1410			100
40		950	1040	1135	1230	1320			
320/85 R28 TL 124A8/121B									
30	1110	1230	1350	1470	1590	1710			128
40		1150	1260	1375	1490	1600			
340/85 R28 TL 127A8/124B									
30	1220	1350	1480	1610	1740	1870			165
40		1260	1380	1505	1630	1750			
380/85 R28 TL 133A8/130B									
30	1430	1585	1740	1890	2045	2200			204
40		1480	1625	1770	1915	2060			
420/85 R28 TL 139A8/136B									
30	1690	1870	2055	2235	2420	2600			262
40		1750	1920	2090	2260	2430			
380/85 R30 TL 135A8/132B									
30	1520	1680	1845	2005	2170	2330			214
40		1570	1720	1875	2030	2180			
420/85 R30 TL 140A8/137B									
30	1740	1930	2115	2305	2490	2680			285
40		1800	1975	2150	2325	2500			
460/85 R30 TL 145A8/142B									
30	2020	2235	2450	2670	2885	3100			345
40		2090	2290	2495	2700	2900			
320/85 R32 TL 126A8/123B									
30	1180	1310	1435	1565	1690	1820			153
40		1220	1340	1460	1580	1700			
420/85 R34 TL 142A8/139B									
30	1840	2040	2240	2440	2640	2840			293
40		1910	2095	2280	2465	2650			
460/85 R34 TL 147A8/144B									
30	2140	2370	2600	2830	3060	3290			390
40		2210	2430	2645	2860	3080			
320/85 R36 TL 128A8/125B									
30	1250	1385	1520	1660	1795	1930			165
40		1300	1425	1550	1675	1800			
340/85 R36 TL 132A8/129B									
30	1390	1540	1690	1840	1990	2140			192
40		1440	1580	1720	1860	2000			
340/85 R38 TL 133A8/130B									
30	1430	1585	1740	1890	2045	2200			210
40		1480	1625	1770	1915	2060			
420/85 R38 TL 144A8/141B									
30	1950	2160	2370	2580	2790	3000			322
40		2020	2215	2410	2605	2800			
460/85 R38 TL 149A8/146B									
30	2260	2505	2750	2990	3235	3480			417
40		2340	2570	2795	3020	3250			
520/85 R38 TL 155A8/152B									
30	2700	2990	3280	3570	3860	4150			518
40		2790	3060	3335	3610	3880			
520/85 R42 TL 157A8/157B									
30	2870	3180	3485	3795	4100	4410			548
40		2970	3260	3550	3835	4125			

Standard specialized

KLEBER SUPER VIGNE***									
Pressures (bar) & Max. load (kg) per Tyre - Take into account the load and type of work when adjusting pressures									
SPEED									Capacity in litres
in km/h	0,6	0,8	1,0	1,2	1,4	1,6			of water 75% max
11.2R20 TL 111A8									
30	780	860	935	1015	1090	1170			74
40			870	945	1015	1090			
9.5R24 TL 107A8									
30	690	760	830	900	970	1040			60
40			780	845	915	980			
11.2R24 TL 114A8									
30	840	925	1010	1090	1175	1260			88
40			940	1020	1100	1180			
13.6R24 TL 121A8									
30	1030	1135	1240	1340	1445	1550			142
40			1160	1255	1355	1450			
14.9R24 TL 126A8									
30	1160	1290	1425	1555	1690	1820			174
40		1200	1325	1450	1575	1700			
9.5R28 TL 109A8									
30	730	805	880	950	1025	1100			76
40			820	890	960	1030			
11.2R28 TL 116A8									
30	890	980	1070	1160	1250	1340			98
40			1000	1085	1165	1250			
12.4R28 TL 121A8									
30	1030	1135	1240	1340	1445	1550			122
40			1160	1255	1355	1450			
13.6R28 TL 123A8									
30	1100	1210	1325	1435	1550	1660			150
40			1240	1345	1445	1550			
14.9R28 TL 128A8									
30	1220	1360	1505	1645	1790	1930			196
40		1270	1400	1535	1670	1800			

Narrow

KLEBER SUPER 3									
Pressures (bar) & Max. load (kg) per Tyre - Take into account the load and type of work when adjusting pressures									
SPEED									Capacity in litres
in km/h	1,6	2,0	2,4	3,0	3,2	3,6			of water 75% max
210/95R32 (8.3R32) ** TL 114A8/114B									
25	1110	1210	1310						
40	1000	1090	1180						
230/95R32 (9.5R32) **** TL 126A8/126B									
25	1280	1395	1510	1680	1750	1890			
40	1150	1255	1360	1510	1575	1700			
270/95R32 (11.2R32) **** TL 134A8/134B									
25	1610	1750	1890	2125	2200	2350			
40	1450	1575	1700	1920	1985	2120			
230/95R36 (9.5R36) **** TL 128A8/128B									
25	1350	1480	1610	1790	1860	2000			
40	1215	1330	1450	1610	1675	1800			
270/95R36 (11.2R36) **** TL 137A8/137B									
25	1720	1860	2000	2300	2385	2550			
40	1550	1675	1800	2075	2150	2300			
270/95R38 (11.2R38) **** TL 138A8/138B									
25	1780	1915	2050	2370	2455	2620			
40	1600	1725	1850	2135	2210	2360			
230/95R40 (9.5R40) ** TL 122A8/122B									
25	1430	1550	1670						
40	1285	1390	1500						
210/95R44 (8.3R44) ** TL 120A8/120B									
25	1310	1430	1550						
40	1180	1290	1400						
230/95R44 (9.5R44) **** TL 132A8/132B									
25	1510	1645	1780	2010	2080	2220			
40	1360	1480	1600	1810	1875	2000			
270/95R44 (11.2R44) **** TL 141A8/141B									
25	1890	2055	2220	2530	2640	2865			
40	1700	1850	2000	2280	2380	2575			
300/95R46 (12.4R46) **** TL 146A8/146B									
25	2290	2495	2700	3040	3135	3330			
40	2060	2245	2430	2740	2825	3000			
230/95R48 (9.5R48) **** TL 134A8/134B									
25	1610	1720	1830	2125	2200	2350			
40	1450	1550	1650	1920	1985	2120			
270/95R48 (11.2R48) **** TL 142A8/142B									
25	2000	2175	2350	2650	2745	2940			
40	1800	1960	2120	2390	2475	2650			
300/95R52 (12.4R52) **** TL 149A8/149B									
25	2330	2640	2860	3235	3360	3610			
40	2180	2380	2575	2910	3025	3250			
270/95R54 (11.2R54) **** TL 144A8/144B									
25	2160	2325	2490	2860	2945	3110			
40	1950	2095	2240	2575	2650	2800			

Standard specialized

KLEBER SUPER VIGNE*									
Pressures (bar) & Max. load (kg) per Tyre - Take into account the load and type of work when adjusting pressures									
SPEED									Capacity in litres
in km/h	1,0								